

## HWAT SELF-REGULATING HEATING CABLE



nVent RAYCHEM HWAT self-regulating trace heating cables maintain water temperatures in a building's hot water distribution network. Installed underneath the thermal insulation, they automatically compensate for pipe heat losses where they occur and provide an energy efficient solution.

### FEATURES & BENEFITS

Simple to design: single pipe instead of recirculation system

Branch lines, instant hot water at tap: for reduced tap times and water waste, water maintained at specific temperatures, no return pipework or return of cold water into the water heater

Easy to install: cut to length, meter marks, simple fast RayClic connections

Energy efficient and safe: no overheating, advanced energy saving and monitoring with HWAT-ECO or ACS-30 controller

Reliable during long life: 10 year product warranty available, aluminum foil layer to protect from chemical ingress, maintenance free

### SPECIFICATIONS

**Conductor Material** Nickel-Plated Copper

**Outer Jacket Material** Modified Polyolefin

**Ground Path Type** Braid

Table 1/1

Catalog Number	Item Name	Supply Voltage	Color	Max Circuit Length	Nominal Width	Nominal Thickness
258015-000	HWAT-L	220 – 240 V	Yellow	180 m	13.8 mm	6.8 mm

Catalog Number	Item Name	Supply Voltage	Color	Max Circuit Length	Nominal Width	Nominal Thickness
2000002863		100 – 120 V	Brown	111 m	18 mm	9.9 mm
266435-000	HWAT-R	220 – 240 V	Red	100 m	16.1 mm	6.7 mm
498639-000	HWAT-M	220 – 240 V	Orange	100 m	13.7 mm	7.6 mm
018662-000	HWAT-M- SPOOLBOX-50	220 – 240 V	Orange	100 m	13.7 mm	7.6 mm

Requires the use of a 30 mA residual current device (RCD) to provide maximum safety and protection from fire. All heating circuits have to be protected by C-type circuit breaker.

#### North America

Tel +1.800.545.6258  
 Fax +1.800.527.5703  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

#### Europe, Middle East, Africa

Tel +32.16.213.511  
 Fax +32.16.213.604  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

#### Asia Pacific

Tel +86.21.2412.1688  
 Fax +86.21.5426.3167  
[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

#### Latin America

Tel +1.713.868.4800  
 Fax +1.713.868.2333  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.  
 nVent reserves the right to change specifications without notice.