

SPECIFICATION GUIDELINE ELECTRONIC THERMOSTAT FOR THE HOT WATER TEMPERATURE MAINTENANCE AND TEMPERATURE MONITORING OF HOT WATER PIPES IN SMALL SYSTEMS OR FOR BRANCH LINES



ENERGY EFFICIENT CONTROL & MONITORING

All nVent RAYCHEM HWAT circuits up to 50 m shall be controlled via an energy saving, electronic thermostat to provide an adjustable maintained temperature in the range of 50-65°C for hot water pipes

THE CONTROLLER SHALL HAVE THE FOLLOWING FUNCTIONS

- Temperature control via pipe line sensors, 10 m probe length:
 - Mounting on DIN rail (35 mm)
 - Manual on / off
- Easy to read digital display with temperature and Visual alarm display
- 3 operating modes: On, Eco, OFF
- 3 temperature settings: 55 ° C, 50 ° C, 45 ° C - easily selected; adjustable
- Timer Function for Eco-mode for additional energy savings
- Reading the actual line temperature
- Protection of the hot water pipe from over temperature
- Low temperature alarm message
- Changeover contact alarm relay for external alarm indication (eg BMS)
- For heating cable HWAT L / M / R to. max. 50 m
- Installation in sub-distribution panel
- VDE mark

United Kingdom

Tel 0800 969 013
Fax 0800 968 624
salesthermalUK@nvent.com

Ireland

Tel 1800 654 241
Fax 1800 654 240
salesIE@nvent.com

South East Asia

Tel +65 67685800
Fax +65 67322263

Australia

Tel +61 2 97920250
Fax +61 2 97745931

India - Noida

Tel +91 120 464 9500
Fax +91 120 464 9548
NTMinfome@nvent.com

India - Mumbai

Tel +91 22 6775 8800/01
Fax +91 22 2556 1491
NTMinfome@nvent.com

UAE

Tel +971 4 378 1700
Fax +971 4 378 1777
NTMinfome@nvent.com



nVent.com

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER